

286 2wd

ENGINE	
Mark	Lombardini
Model	LDW 1603 plus serial
Emission class	Eu Stage 3A
Type	3-cylinder diesel in-line engine
Cylinder displacement	1649cm ³
Power	27kW(36hv)/2400 ^r / _{min}
Torgue	113Nm/1600 ^r / _{min}
Other	

POWER TRANSMISSION	
Type	Hydrostatic 2-wheel drive.
Max pulling force	-----
Constructional driving speed	0-10 ^{km} / _h , 0-10 ^{km} / _h low speed area 0-20km/h , 0-10km/h high speed area
Backward and forward	Driving pedal
Other	

WEIGHTS	
Unladen weight front/back	1140kg, 720kg/420kg (63%/37%)
Max front axel mass	1600kg
Max rear axel mass	1200kg
Other	

TYRES	
FRONT	
Mark, model	Hankook
Size	31x11,5-15
Load bearing capacity	1030 kg
Other	
REAR	
Mark, model	Hankook
Size	175/13
Load bearing capacity	475 kg
Other	

ELECTRICAL SYSTEM	
Generator	14V 65 AMP
Accumulators	1kpl 12V 70ah 540A (EN)
Start motor	12V 2,2 kw
Other	

FILLING CAPACITIES	
Fuel tank	35 l
Hydraulic oil tank	55 l
Other	

BRAKES	
Drive brake	Inside front wheelmotors
Parking brakes	Inside front wheelmotors electro-hydraulic
Other	

STEERING	
Type	Rear wheel steering
Turning angle	inside 1025mm outside 2825mm
Control	
Other	

WORK HYDRAULICS	
Pump	Double acting gearpump 19,5 cm ³
Filtering	Returning filter
Control	
Other	

OPTIONS FOR INSTANT FASTENING	
Type	A-frame, 3-point coupling
Lifting force down up	350 kg / 350 kg
Other	

CABIN

Safety cabin approved by ISO 3471

Other

NOISE

Inside

L_{pa} 79dB

Outside

L_{pa} 98dB

Other