LM TRAC 387

LM Trac 387 is a handy machine in city environment. Small turning circle and narrow construction prove effective on cramped streets and alleys.

New, more powerful engine reaches EU stage IIIB / Tier 4 Final emission ratings.

With various tools LM Trac 387 can be used effectively all year round.

New pump design and driving programs minimize fuel consumption.

www.laimu.fi | OY LAI-MU AB

ENGINE AND TRANSMISSION

Engine	Kohler KDI 1903 TCR, turbodiesel. EU stage IIIB, US tier 4 final
Engine displacement	1861cm³
Power	42kW / 56,3bhp (2600rpm)
Torque	225 Nm (1500rpm)
Transmission	Automatic 4WD, traction control
Speed ranges	0-20 km/h & 0-40km/h (0-12mph & 0-25mph)
Driving direction control	Electrical switch
Steering	Hydrostatic articulated steering
Brakes	Drum brakes
Tires	26x12-12
Fuel tank	45 litres (12US Gallons)

WORK HYDRAULICS

Type	Variable pump
Motor hydraulics	0-60 l/min & 0-30 l/min, 200bar
Controls	Joystics and potentiometers
Implement connection	A-frame or 3-point attachment
Hydraulic oil tank	57 litres
Electrical system	12 V

OPTIONAL EQUIPMENT

	Air conditioning, airsuspensioned seat, LED-working lights, Radio/CD player, extra heater, towing equipment, trailer brake system, etc.

DIMENSIONS AND WEIGHT

Length	3100mm
Height	1980mm
Width	1370mm
Weight	1750kg

We reserve the right to modifications without prior notice.

MANUFACTURER:

OY LAI-MU AB
NIITTAAJANTIE 9
FI-26820 RAUMA

TEL: +358 2 8387 2400
FAX: +358 2 8387 2444

www.laimu.fi
laimu@laimu.fi

DISTRIBUTOR: