



**286**



 **LM TRAC**  
LM Trac 286

Oy LAI-MU Ab



[www.laimu.fi](http://www.laimu.fi)

Four seasons, you name the season, LM286 full fill your needs



## WEED STEAMER



Chemical free way to control unwanted weed from streets and pedestrian zones



## WEED BRUSH



Mechanical and environment friendly solution to keep streets clean of weeds and dirt

## ROTARY MOVER



Comfortable solution to cut grass wherever and whenever is needed





LM286 tractor is versatile and agile tool for demanding applications all over the year



### SUCTION UNIT



Optimal application for vacuuming leaves and other rubbish from lawns and streets

### SPINNER SPREADER & SWEEPER



For snowy and icy conditions to keep streets clean and safe



### SWEEPER-SUCTION UNIT & SWEEPER



Keep your environment tidy and dust free by brushing and vacuuming

## TECHNICAL DATA

### ENGINE AND TRANSMISSION

Engine	Kohler / Lombardini LDW1603 CHD Plus, 3-cyl. diesel
Cylinder capacity	1649 cm <sup>3</sup>
Power	27 kw / 2600 rmp (36 hp)
Torque	113 Mm / 1600 rmp
Transmission	Continuous hydrostatic 2-wheel or 4-wheel drive



### DRIVE HYDRAULICS

Output	0-60 ltr/min / 2400 rpm (drive pump)
Pressure	350 bar (drive pump)
Speed ranges	0-11 km/h & 0-22km/h (2WD) 0-6 km/h & 0-12 km/h (4WD)
Forward/reverse selection	Drive pedal
Steering	Hydrostatic rear wheel steering (LS)
Brakes	Hydrostatic, wet disc brakes front, electric parking brake
Tires	31 X 11.5 R15 front, 175 / 13 rear (2WD), 210/10 rear (4WD)
Fuel tank	35 ltr

### WORK HYDRAULICS

Type	Fixed displacement, open system
Engine hydraulics	47 liter/min / 2400 rpm
Pressure MAX	200 bar

### CYLINDER HYDRAULICS

Output	15 ltr/min / 175 bar
Control	Two Mini-Joysticks
Implement connection	A-frame
Hydraulic oil tank	55 ltr
Electrical system	12 V

### OPTIONAL EQUIPMENT

Air-conditioning, Air seat, LED work lights, Radio/CD player, Cabin heater, Rear hydraulics, Hitch, etc.

### DIMENSIONS AND WEIGHT

Length	2680 mm
Height	2095 mm
Width	1340 mm
Turning radius, inner	1025 mm
Ground clearance	180 mm
Dead weight	1140 kg (2WD), 1190 kg (4WD)

We reserve the right to modification without prior notice.

### MANUFACTURER:



Oy LAI-MU Ab tel: +358 2 8387 2400  
Niittaajantie 9 fax: +358 2 8387 2444  
FI-26820 RAUMA laimu@laimu.fi  
www.laimu.fi

### DISTRIBUTOR:

